


Finished Product Style(成品針類型)

PE100-V(90)-10G



Technical Specifications

Recommended Minimum Center	:2.54mm(100mil)
Current Rating	:3amps, continuous
Contact Resistance	:30milliohms
Full Stroke	:6.50mm
Rated Stroke	:4.30mm
Spring Force	:284gf(10 oz)

技術規格簡介

建議採用的最小值中心距	: 2.54mm(100mil)
額定電流	: 3安培, 連續
額定電阻	: 30毫歐姆
滿衝程	: 6.50mm
額定衝程	: 4.30mm
額定彈力	: 284gf(10 oz)

Materials

Contact Barrel	:Brass, Gold Plated
Spring	:Music Wire, Gold Plated
Plunger	:BeCu or Steel, Rhodium Plated to Gold Plated

材 料

接觸筒	: 黃銅, 鍍金
彈 簧	: 琴綫, 鍍金
杆 身	: 鍍銅或鋼, 鍍鎳或鍍金

Tip Style(針頭類型)



How To Order: Spring Contact Probe

PE100	V(90)	10	G
Series	Tip Style	Spring Force (oz)	Plating Options [G-Gold Plated]

Series: PE100  
Tip Style: B(90), K9(90), J(90), U5(90), U(90), IT(90)  
Spring Force: 10 oz

如何訂購: 彈弓測試針

PE100	V(90)	10	G
系列	針頭類型	彈力(oz)	電鍍 (G-鍍金)

系列: PE100  
頭型: B(90), K9(90), J(90), U5(90), U(90), IT(90)  
彈力: 10 oz